

Installation

It will take a minimum of 2 people to properly install the Rearz film on your window. The temperature must be between 45° and 90° Fahrenheit in order for the adhesive bond to form correctly. Glass must be completely CLEAN and DRY before the installation.

You will need the following items in order to properly install your window graphic:

- 1) Soap & Water to clean the window
- 2) A soft, clean lint-free cotton cloth
- 3) A new, sharp razor for trimming to size
- 4) Masking tape

Preparing the Surface:

The window must be thoroughly cleaned before film is applied. Clean the glass using soapy water, and then thoroughly rinse the window. Be sure that the window is completely free from any remaining soap residue.

DO NOT USE ANY CHEMICAL BASED WINDOW CLEANERS AS THIS MAY REACT NEGATIVELY WITH THE ADHESIVE.



Installation:

Before removing backing material, unroll the graphic and select the position on the window that is desired. You may wish to use masking tape along the top edge to temporarily hold the graphic in the desired position.



Once desired placement is selected, position 1 person on either side of the window and carefully begin removing the backing material starting from the top and working your way to the bottom. **WARNING: DO NOT STRETCH THE MATERIAL. THIS WILL CAUSE THE PRODUCT TO CURL AND LIFT FROM THE WINDOW AFTER IT IS INSTALLED.** While peeling away backing material, gently smooth the film against the window.



If air bubbles form during this process, gently lift the material and reapply while smoothing the bubble area. Once graphic is completely flat against the window and all wrinkles and air bubbles are removed, start from the center of the glass and gently rub the entire area with a soft, clean, lint-free towel to secure the adhesive to the glass.



Carefully trim with the razor blade the excess material around the perimeter of the window trim. **WARNING: USE EXTREME CAUTION WHEN TRIMMING TO AVOID INJURY AND TO AVOID DAMAGE TO THE VEHICLE.** Discard excess material.



Removal Instructions:

The product can be easily removed by starting at one corner and peeling the film from the window. If necessary, use a plastic scrapper to help loosen the material from the glass, then peel away from the window. Remaining residue can be easily removed with a glass cleaner.



WARNINGS

Do NOT use an ice scrapper on the rear window or risk of damage to the film may occur. This product was to be applied to the OUTSIDE of the rear window only. This product requires trimming with a sharp razor blade.

Use extreme caution when using any sharp objects as they can cause severe injury. Take extreme care not to damage any surrounding area of the vehicle when trimming the excess. Excessive heat and/or cold temperature exposure will reduce the life of the adhesive. Glass can be easily scratched. Use extreme caution when using the razor blade on the glass surface. This product is to be applied on the rear window ONLY.

This product is not to be applied to any other window of the vehicle as it may significantly obstruct visibility and create a significant safety hazard. Do NOT operate windshield wipers on glass with the window graphics installed. This could damage both the window graphic as well as the wiper. Installing this product may reduce or impair visibility.

WARNING: State and Local laws may prohibit the use of window film being installed on your vehicle. Please check your local and state regulations to verify that the use of this product is approved. This product is to be applied to the OUTSIDE of the rear window ONLY. This product is not to be applied to any other window of the vehicle as it may obstruct visibility and create a safety hazard. This product requires trimming with a sharp razor blade. Use extreme caution when using any sharp objects as they can cause severe injury. Take extreme care not to damage any surrounding area of the vehicle when trimming the excess. Install this product only in strict accordance with the provided instructions. Installing this product may reduce or impair visibility.

Warranty

IN-concept products are manufactured under quality control standards and are guaranteed to be

free from defects in material and workmanship. Any material that is shown to be defective upon receipt of the product will be replaced without charge.

LIMITATION OF LIABILITY; INDEMNIFICATION

PURCHASER AGREES THAT IN NO EVENT SHALL IN-CONCEPT BE RESPONSIBLE FOR ANY DAMAGES BEYOND THE REPLACEMENT OF ANY DEFECTIVE PRODUCT IN ACCORDANCE WITH THE PRECEDING WARRANTY, AND THAT IN NO EVENT SHALL IN-CONCEPT BE LIABLE OR RESPONSIBLE FOR DAMAGES OF ANY KIND WHATSOEVER THAT MAY RESULT FROM THE USE OR INSTALLATION OF THIS PRODUCT. PURCHASER SHALL INDEMNIFY IN-CONCEPT AGAINST ANY CLAIMS MADE AGAINST IN-CONCEPT BY ANY OTHER PERSON RESULTING FROM PURCHASER'S USE OR OWNERSHIP OF THE PRODUCT. IF PURCHASER DOES NOT AGREE TO THESE TERMS, PLEASE RETURN THE PRODUCT IN ITS ORIGINAL PACKAGING WITHIN THIRTY (30) DAYS FROM THE DATE OF PURCHASE FOR A FULL REFUND.